

DESCRIPTION				
Total thickness	ISO 24346 EN 428	mm	2.0	3*
Weight	ISO 23997 EN 430	g/sq.m	3150	3950
Width/length of sheet	ISO 23441 EN 426	lm	20	20
CLASSIFICATION				
Norm / product specification	-	-	ISO 10581 EN 649	
European classification	ISO 10874 EN685	class	34-43	
Fire rating	EN ISO 9239-1 EN ISO 11925-2	class	Bfl-s1	
Static electrical propensity	EN 1815	kV	< 2	
Electrical resistance	EN 1081	Ω	10 <sup>9</sup> 10 <sup>10</sup>	
Slip resistance dry	EN 13893	-	≥ 0.3	
Slip resistance wet	DIN 51130	class	R9	
Toxic testing	GB 18586 - 2001	good	good	
PERFORMANCE				
Type binder content	ISO 10581	Type	II	
Wear group	EN 649	group	P	
Dimensional stability	ISO 23999 EN 434	%	≤ 4.0	
Castor chair test	ISO 4918 EN 425	-	OK	
Thermal conductivity	ISO 10456 EN 12524	W/(m.K)	=0.25	
Colour fastness	ISO 105 - B02	degree	≥ 6	
Chemical product resistance	ISO 26987 EN 423	-	OK	
Antit-bacterial activity	JIS Z 2801	-	99% Inhibits growth	
Residual indentation	EN 433	mm	Approx.0.04	
Decontamination rated	ISO 8690	-	Good	
Surface treatment	-	-	PUR+ Iodine stain free	
Colour number	-	-	28	
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000 - 6	µg/m <sup>3</sup>	< 10	
CE MARKING				
		   		

\* Available in 3mm thickness. Special order with MOQ

Be connected!



#Jeoflor



## Jeoflor

Our related products!



Floor  
Self Leveling



Wall Coverings  
& Protections



Skirting &  
Profiles



Handrails



# Jeoflor

Alptahls GmbH, Bürgergasse 4, 8330 Feldbach, Austria. 

Tel. +43 (0)3152 370 49

info@jeoflor.com www.jeoflor.com

Toll Free : 18002028498