

TECHNICAL SPECIFICATIONS

CLASSIC+

DESCRIPTION			
Total thickness	ISO 24346 (EN 428)	mm	2.0*
Wearlayer thickness	ISO 24340 (EN 429)	mm	0.3
Weight	ISO 23997 (EN 430)	g/m ²	3150
Width of sheet	ISO 24341 (EN 426)	lm	20
Length of sheet	ISO 24341 (EN 426)	lm	
CLASSIFICATION			
Norm / Product specification	-	-	ISO 10582 (EN 649) 34-43
European classification	ISO 10874 (EN 685)	class	Bfl-s1
Fire rating	EN 13501 - 1	class	<2
Static electrical propensity	EN 1815	kV	R10
Slip resistance wet	DIN 51 130	class	
PERFORMANCES			
Type binder content	ISO 10582	type	≤ 0.4
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.1
Residual indentation	ISO 24343-1 (EN 433)	mm	OK
Castor chair test	ISO 4918 (EN 425)	-	0.25
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.k)	≥ 6
Colour fastness	ISO 105 - B02	degree	OK
Chemical product resistance	ISO 26987 (EN 423)	-	Pur+ Protected
Surface treatment	-	-	>99% inhibits growth
Anti-bacterial activity (E.coli - S.aureus - MRSA)	JIS Z 2801	-	99.7% after 5h
Antiviral activity (human coronavirus 229E)	ISO 21702	-	
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000 - 6	µg/m	<100
CE MARKING			
	EN 14041	   	

The implementation of an effective cleaning regime is the most important defence against infections.

Be connected!



#Jeoflor



Our related products!



Floor
Self Leveling



Wall Coverings
& Protections



Skirting &
Profiles



Handrails



LCA

Eco-designed according to a product specific Life Cycle Analysis



WELLNESS

Walking comfort < 75 dB



REACH

COMPOSITION
100% REACH compliant



INDOOR AIR QUALITY

TVOC emissions 100 times better than norm requirements (TVOC < 10 µg/m³ after 28 days)



RECYCLABILITY

100%



RECYCLED CONTENT

25%

Jeoflor

Alptahls GmbH, Bürgergasse 4, 8330 Feldbach, Austria. =

Tel. +43 (0)3152 370 49

info@jeoflor.com www.jeoflor.com

Toll Free : 18002028498

