




DESCRIPTION			
Total thickness	ISO 24346 (EN 428)	mm	2.0*
Wearlayer thickness	ISO 24340 (EN 429)	mm	0.5
Weight	ISO 23997 (EN 430)	g/m ²	2800
Width of sheet	ISO 24341 (EN 426)	lm	2
Length of sheet	ISO 24341 (EN 426)	lm	20
CLASSIFICATION			
Norm / Product specification	-	-	ISO 10582 (EN 649)
European classification	ISO 10874 (EN 685)	class	34-43
Fire rating	EN 13501 - 1	class	Bfl-s1
Static electrical propensity	EN 1815	kV	<2
Slip resistance wet	DIN 51 130	class	R10
PERFORMANCES			
Type binder content	ISO 10582	type	I
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.4
Residual indentation	ISO 24343-1 (EN 433)	mm	≤ 0.1
Castor chair test	ISO 4918 (EN 425)	-	OK
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.k)	0.25
Colour fastness	ISO 105 - B02	degree	≥ 6
Chemical product resistance	ISO 26987 (EN 423)	-	OK
Surface treatment	-	-	Pur+ Protected
Anti-bacterial activity (E.coli - S.aureus - MRSA)	JIS Z 2801	-	>99% inhibits growth
Antiviral activity (human coronavirus 229E)	ISO 21702	-	99.7% after 5h
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000 - 6	µg/m	<100
CE MARKING			
	EN 14041		
			

* Available in 2.6/3/4/5mm thickness. Special order with MOQ
 The implementation of an effective cleaning regime is the most important
 defence against infections.