

JEO ESD ROLL

JEO ESD TILE

DESCRIPTION				
Total thickness	EN 428	mm	2.0	2.0/3*
Weight	EN 430	g/sq.m	2900	3440
Width/length of sheet	EN 426	cm / lm	200 / 20	-
Tile size	EN 427	mm	-	608 x608
Number of tiles per package	-	-	-	20
CLASSIFICATION				
Standard / product specification	-	-	EN10581	EN10581
European classification	EN 685	class	34-43	34-43
Fire rating	EN 13501-1	class	Bfl - s1	Bfl - s1
Electrical resistance	EN 1081	Ohm	$10^4 \leq Rt \leq 10^6$	$10^4 \leq Rt \leq 10^6$
Static electrical propensity	EN 1815	kV	< 2	< 2
Slip resistance wet	DIN 51 130/BGR 181	class	R9	R9
PERFORMANCE				
Wear resistance	EN 660.2	mm ³	≤ 4.0	≤ 4.0
Wear group	NF 189	-	T	P
Type binder content	EN ISO 10581	Type	I	II
Dimensional stability	EN 434	%	≤ 0.40	≈ 0.25
Residual indentation	EN 433	mm	≈ 0.03	≈ 0.03
Castor chair test (Type W)	EN 425	-	OK	OK
Thermal conductivity	EN 12 524	W/(m.K)	0.25	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6	≥ 6
Chemical resistance	EN 423	-	OK	OK
Surface treatment	-	-	Pur+ Protected	Pur+ Protected
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000-6	$\mu\text{g}/\text{m}^3$	< 10	< 10
CE MARKING				
CE	EN 14041			

* Available in 3mm thickness. Special order with MOQ

Be connected!



#Jeoflor



Our related products!



Floor Self Leveling



Wall Coverings & Protections



Skirting & Profiles



Handrails



LCA

Eco-designed according to a product specific Life Cycle Analysis



WELLNESS

Walking comfort < 75 dB



REACH

COMPOSITION

100% REACH compliant



INDOOR AIR QUALITY

TVOC emissions 100 times better than norm requirements (TVOC < 10 $\mu\text{g}/\text{m}^3$ after 28 days)



RECYCLABILITY

100%



RECYCLED CONTENT

25%

Jeoflor

Alptahls GmbH, Bürgergasse 4, 8330 Feldbach, Austria. =

Tel. +43 (0)3152 370 49

info@jeoflor.com www.jeoflor.com

Toll Free : 18002028498

