

DESCRIPTION			
Total thickness	EN 428	mm	2.0
Weight	EN 430	g/sq.m	2900
Width/length of sheet	EN 426	cm / lm	200 / 20
CLASSIFICATION			
Standard / product specification	-	-	EN10581
European classification	EN 685	class	34-43
Fire rating	EN 13501-1	class	Bfl - s1
Electrical resistance	EN 1081	Ohm	$10^4 \leq R_t \leq 10^6$
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet	DIN 51 130/BGR 181	class	R9
PERFORMANCE			
Wear resistance	EN 660.2	mm <sup>3</sup>	≤ 4.0
Wear group	NF 189	-	T
Type binder content	EN ISO 10581	Type	I
Dimensional stability	EN 434	%	≤ 0.40
Residual indentation	EN 433	mm	≈ 0.03
Castor chair test (Type W)	EN 425	-	OK
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical resistance	EN 423	-	OK
Surface treatment	-	-	RHPP+ Protected
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/m <sup>3</sup>	< 10
CE MARKING			
CE	EN 14041	   	

### Be connected!



#Jeoflor



### Our related products!



Floor  
Self Leveling



Wall Coverings  
& Protections



Skirting &  
Profiles



Handrails



LCA

Eco-designed according to a product specific Life Cycle Analysis



WELLNESS

Walking comfort < 75 dB



REACH

COMPOSITION  
100% REACH compliant



INDOOR AIR QUALITY

TVOC emissions 100 times better than norm requirements (TVOC < 10 µg/m<sup>3</sup> after 28 days)



RECYCLABILITY

100%



RECYCLED CONTENT

25%

# Jeoflor

Alptahls GmbH, Bürgergasse 4, 8330 Feldbach, Austria. =

Tel. +43 (0)3152 370 49

info@jeoflor.com www.jeoflor.com

Toll Free : 18002028498

