

TECHNICAL SPECIFICATIONS

ELECTRO PREMIUM +

DESCRIPTION			DISSIPATIVE	ESD ROLL	ESD TILE
Total thickness	EN 428	mm	2.0	2.0	2.0/3*
Weight	EN 430	g/sq.m	2900	2900	3440
Width/length of sheet	EN 426	m/lm	2/20	2/20	-
Tile size	EN 427	mm	-	-	608 x608
Number of tiles per package	-	-	-	-	20
CLASSIFICATION					
Standard/product specification	-	-	EN10581	EN10581	EN10581
European classification	EN 685	class	34-43	34-43	34-43
Fire rating	EN 13501-1	class	Bfl-s1	Bfl-s1	Bfl-s1
Electrical resistance	EN 1081	Ohm	10 ⁴ ≤ Rt ≤ 10 ⁸	10 ⁴ ≤ Rt ≤ 10 ⁶	10 ⁴ ≤ Rt ≤ 10 ⁶
Static electrical propensity	EN 1815	kV	<2	<2	<2
Slip resistance wet	DIN 51 130/BGR 181	class	R9	R9	R9
PERFORMANCE					
Wear resistance	EN 660.2	mm ³	≤ 4.0	≤ 4.0	≤ 4.0
Wear group	NF 189	-	T	T	P
Type binder content	EN ISO 10581	Type	II	I	II
Dimensional stability	EN 434	%	≤ 0.40	≤ 0.40	≈0.25
Residual indentation	EN 433	mm	≈0.02	≈0.03	≈0.03
Castor chair test (Type W)	EN 425	-	OK	OK	OK
Thermal conductivity	EN 12 524	W/(m.K)	0.25	0.25	0.25
Colour fastness	EN 20 105-B02	degree	≥6	≥6	≥6
Chemical resistance	EN 423	-	OK	OK	OK
Impact sound reduction	EN ISO 10140/1 EN ISO 717/2		Approx.+8DB	Approx.+8DB	Approx.+8DB
Surface treatment		UV and antibacterial protected		Premium Diamond shield Anti Iodine stain free	
ENVIRONMENT / INDOOR AIR QUALITY					
TVOC after 28 days	ISO 16000 - 6	µg/m ³	<10	<10	<10
CE MARKING					
 EN 14041					

Jeoflor has a policy of continuous product improvement, it reserves the right to change design and specifications without notice.

***Available in 3mm thickness. Special order with MOQ**
REMARK : Product colors may slightly vary from batch to batch.
The implementation of an effective cleaning regime is the most important defence against infections.

Be connected



#Jeoflor



Our related products



Floor
Self Leveling



Wall Coverings
& Protections



Skirting &
Profiles



Handrails



Jeoflor®

Alptahls GmbH, Bürgergasse 4, 8330 Feldbach, Austria. 
Tel. +43 (0)3152 370 49
info@Jeoflor.com www.Jeoflor.com
Toll Free : 18002028498