


## TECHNICAL DATA

Description	Standard	Requirement	Units	Results
Surface treatment	-	-	-	UV
Top layer	-	-	mm	.85
Thickness	EN ISO 24346	-	mm	3.25 to 4.5
Width	EN ISO 24341	-	lm	1.5
Length	EN ISO 24341	-	lm	15
Weight	EN ISO 23997	-	kg/m <sup>2</sup>	3240
<b>Technical Characteristics</b>				
Abrasion resistance	EN ISO 5470-1			≤ 350
Impact resistance	EN 1517	≤ 1000	mg	≥ 8
Indentation resistance	EN 1516	≥ 8	N/m	≤ 0.5
Sound Insulation	EN ISO 717-2	DB	-	19 to 25
<b>Classification</b>	EN 13501-1	≤ 0.5	mm	
Fire	ISO 22196	-	-	Cfl-s1
Anti-bacterial activity (E. coli - S. aureus - MRSA)		-	-	> 99% inhibits growth
<b>CE Marking</b>	EN 14 904	-	-	
				Fire Sliding Coefficient Abrasion Resistance Rolling load Resistance

The proposed specifications fall within the tolerance limits usually accepted in this sector whilst still complying with standards.

(1) The implementation of an effective cleaning method is the best defence against infection

\* For different roll lengths please contact us

