

TECHNICAL SPECIFICATIONS

DESCRIPTION			
Total thickness	EN 428	mm	2.0
Weight	EN 430	g/m ²	2950
Width of sheet	EN 426	m	2
Length of sheet	EN 426	lm	20
CLASSIFICATION			
European classification	EN 685	Class	34-43
Fire rating	GB 8624-2012		Bfl-s1
Toxic testing	GB 18586-2001		Good
Static electrical propensity	EN 1815	KV	≥ 2
Electrical resistance / Anti Static	EN 1081	Ω	>10 ¹¹
Slip resistance wet	EN 51130		R9
Slip resistance dry	EN 13893	Class	≥ 0.3
PERFORMANCES			
Dimensional stability	EN 434	%	≤ 0.40
Thermal conductivity	EN 12524	W/(m.k)	0.25
Castor wheel test	EN 425	-	OK
Wear resistance	EN 660.2	mm ³	≤ 2.0
Abrasion Group	EN 660-2	group	T
Type binder content	ISO 10581	type	I
Residual indentation	EN 433	mm	≈0.04
Colour fastness	EN 20 105 B02	degree	≥ 6
Chemical product resistance	EN 423	class	Good
Clean room	ISO 14644-1	class	3
Antibacterial property MRSA	ISO 22196	-	>99% inhibits growth
Flexibility	EN 435	-	Excellent
Decontamination rated	EN 435		Very good
Surface treatment	-	UV and antibacterial protected	Premium Diamond shield Anti Iodine stain free
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000 - 6	-µg/m ³	<10
CE MARKING			
		    	

Jeoflor has a policy of continuous product improvement, it reserves the right to change design and specifications without notice.

REMARK : Product colour will be slight variation batch from batch.

The implementation of an effective cleaning regime is the most important defence against infections.

Be connected!



#Jeoflor



Our related products!



Floor
Self Leveling



Wall Coverings
& Protections



Skirting &
Profiles



Handrails



Jeoflor®

Alptahls GmbH, Bürgergasse 4, 8330 Feldbach, Austria. 

Tel. +43 (0)3152 370 49

info@Jeoflor.com www.Jeoflor.com

Toll Free : 18002028498