







TECHNICAL SPECIFICATIONS

| DESCRIPTION | | | |
|---|---------------------------------|---|---|
| Total thickness | EN 428 | mm | 2.0 |
| Weight | EN 430 | g/m ² | 2850 |
| Width of sheet | EN 426 | m | 2 |
| Length of sheet | EN 426 | lm | 20 |
| CLASSIFICATION | | | |
| European classification | EN 685 | | 23-33 |
| Fire rating | EN ISO 9239-1 EN ISO 11925-2 | Class | Bfl-s1 |
| Toxic testing | GB 18586-2001 | | Good |
| Static electrical propensity | EN 1815 | KV | ≤ 2 |
| Electrical resistance / Anti Static | EN 1081 | Ω | 10 ⁹ -10 ¹⁰ |
| Slip resistance | DIN 51130 | Class | R9 |
| PERFORMANCES | | | |
| Dimensional stability | EN 434 | % | ≤ 0.4 |
| Thermal conductivity | EN 12524 | W/(m.k) | 0.25 |
| Castor wheel test | EN 425 | - | OK |
| Wear resistance | EN 660.2 | mm ³ | ≤ 2.0 |
| Abrasion Group | EN 649 | group | T |
| Type binder content | ISO 10581 | type | I |
| Residual group | EN 433 | mm | ≈ 0.02 |
| Colour fastness | EN 20 105 B02 | degree | ≥ 6 |
| Chemical product resistance | EN 423 | class | OK |
| Antibacterial property MRSA | ISO 22196 | - | >99% inhibits growth |
| Flexibility | ISO 8690 | - | Good |
| Decontamination rated | EN 435 | - | Very good |
| Impact sound reduction | EN ISO 10140/1 EN ISO 717/2 | - | Approx.+4DB |
| Surface treatment | - | UV Protected | PUR+ Iodine stain free |
| ENVIRONMENT / INDOOR AIR QUALITY | | | |
| TVOC after 28 days | ISO 16000 - 6 | µg/m ³ | <10 |
| CE MARKING | | | |
|  | EN 14041 |  |  DS  Bfl-s1  |



Be connected!



#Jeoflor



Our related products!



Floor
Self Leveling



Wall Coverings
& Protections



Skirting &
Profiles



Handrails



Jeoflor

Alptahls GmbH, Bürgergasse 4, 8330 Feldbach, Austria. =

Tel. +43 (0)3152 370 49

info@jeoflor.com www.jeoflor.com

Toll Free : 18002028498