

HOMOGENEOUS VINYL FLOORING

Premium+



Jeoflor
AUSTRIA




34-43




0950 Cotton 



0951 Breeze 



0952 Mole 





0953 Chocolate 



0954 Musk 



0955 Grey Stone 






0956 Pebble 



0957 Cloud 



Premium+



0958 Stone





0959 Sunshine



0960 Twilight



0961 Sunset



0962 Light Ocre



0963 Mustard



0964 Rosa




0965 Tomatoe






34-43




0966 Sapphire




0967 Mix Blue



0968 Green Apple



0969 Lagoon




0970 Emerald Green




0971 Cumin



0972 Lavender



0973 Blue Crop



0974 Sand





LCA



- Manufactured in an ISO 14001: 2015 certified
- Product specific EPD (Environmental Products Declaration) available
- Eco-designed according to a product specific Life Cycle Analysis
- Contribution to many Green Building Schemes
- Surface treatment PUR+ Iodine free protected to reduce drastically the use of chemical products and water and ensure the lowest environmental impact

WELLNESS



Health

- Antibacterial activity (Inhibits growth > 99%)

Comfort

- Walking comfort < 75 dB

RECYCLABILITY



- 100% recyclable product

INDOOR AIR QUALITY



- TVOC emissions 100 times better than norm requirements (TVOC < 10 µg/m³ after 28 days)
- SGS certified
- No formaldehyde emission

COMPOSITION

100% REACH compliant








- FREE of formaldehyde
- FREE of heavy metals
- FREE of Solvent

RECYCLED CONTENT



- 100% REACH compliant recycled content

TECHNICAL SPECIFICATIONS

DESCRIPTION			
Total thickness	EN 428	mm	2.0
Weight	EN 430	g/m ²	2800
Width of sheet	EN 426	m	2
Length of sheet	EN 426	lm	20
CLASSIFICATION			
European classification	EN 685		23-33
Fire rating	EN ISO 9239-1 EN ISO 11925-2	Class	Bfl-s1
Toxic testing	GB 18586-2001		Good
Static electrical propensity	EN 1815	KV	≤ 2
Electrical resistance / Anti Static	EN 1081	Ω	10 ⁹ -10 ¹⁰
Slip resistance	DIN 51130	Class	R9
PERFORMANCES			
Dimensional stability	EN 434	%	≤ 0.4
Thermal conductivity	EN 12524	W/(m.k)	0.25
Castor wheel test	EN 425	-	OK
Wear resistance	EN 660.2	mm ³	≤ 2.0
Abrasion Group	EN 649	group	T
Type binder content	ISO 10581	type	I
Residual group	EN 433	mm	≈ 0.02
Colour fastness	EN 20 105 B02	degree	≥ 6
Chemical product resistance	EN 423	class	OK
Antibacterial property MRSA	ISO 22196	-	>99% inhibits growth
Flexibility	ISO 8690	-	Good
Decontamination rated	EN 435	-	Very good
Impact sound reduction	EN ISO 10140/1 EN ISO 717/2	-	Approx.+4DB
Surface treatment	-	UV Protected	PUR+ Iodine stain free
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000 - 6	µg/m ³	<10
CE MARKING			
	EN 14041		 DS  Bfl-s1 

The implementation of an effective cleaning regime is the most important defence against infections.

Be connected!



#Jeoflor



Our related products!



Floor
Self Leveling



Wall Coverings
& Protections



Skirting &
Profiles



Handrails



Jeoflor

Alptahls GmbH, Bürgergasse 4, 8330 Feldbach, Austria. 

Tel. +43 (0)3152 370 49

info@jeoflor.com www.jeoflor.com

Toll Free : 18002028498