






## TECHNICAL SPECIFICATIONS

| DESCRIPTION                                                                         |                     |                                                                                                                                                                                                                                                                                                                                                         |                    |
|-------------------------------------------------------------------------------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|
| Total thickness                                                                     | EN 428              | mm                                                                                                                                                                                                                                                                                                                                                      | 2.00               |
| Thickness of wear layer                                                             | EN 429              | mm                                                                                                                                                                                                                                                                                                                                                      | 0.55               |
| Weight                                                                              | EN 430              | g/m <sup>2</sup>                                                                                                                                                                                                                                                                                                                                        | 2300               |
| Length / Width                                                                      | EN 426              | cm/ml                                                                                                                                                                                                                                                                                                                                                   | 20 / 2             |
| CLASSIFICATION                                                                      |                     |                                                                                                                                                                                                                                                                                                                                                         |                    |
| Product norm                                                                        |                     |                                                                                                                                                                                                                                                                                                                                                         | EN 651             |
| European                                                                            | EN 685              |                                                                                                                                                                                                                                                                                                                                                         | 34-42              |
| Walking resonance                                                                   | NF S 31-074         | db                                                                                                                                                                                                                                                                                                                                                      | Class A            |
| Sound insulation                                                                    | EN ISO 717-2        | db                                                                                                                                                                                                                                                                                                                                                      | 17                 |
| Fire rating                                                                         | EN 13501-1          |                                                                                                                                                                                                                                                                                                                                                         | C <sub>s</sub> -s1 |
|                                                                                     | NFP 92506           |                                                                                                                                                                                                                                                                                                                                                         | M3                 |
|                                                                                     | DIN 4102            |                                                                                                                                                                                                                                                                                                                                                         | B1                 |
| Static electrical charge                                                            | EN 1815             | kV                                                                                                                                                                                                                                                                                                                                                      | <2 (anti-static)   |
| Slip resistance dry                                                                 | EN 13893            |                                                                                                                                                                                                                                                                                                                                                         | ≥ 0.3              |
| Slip resistance wet                                                                 | EN 51130            |                                                                                                                                                                                                                                                                                                                                                         | R9                 |
| PERFORMANCE                                                                         |                     |                                                                                                                                                                                                                                                                                                                                                         |                    |
| Abrasion resistance                                                                 | EN 660.1            |                                                                                                                                                                                                                                                                                                                                                         | ≤ 0.08             |
| Abrasion group                                                                      |                     |                                                                                                                                                                                                                                                                                                                                                         | T                  |
| Dimensional stability                                                               | EN 434              | %                                                                                                                                                                                                                                                                                                                                                       | ≤ 0.4              |
| Indentation - Exigency                                                              | EN 433              | mm                                                                                                                                                                                                                                                                                                                                                      | ≤ 0.20             |
| Indentation - Measure                                                               |                     | mm                                                                                                                                                                                                                                                                                                                                                      | 0.15               |
| Thermal resistance                                                                  | NFX 10021/DIN 52612 | m <sup>2</sup> K/W                                                                                                                                                                                                                                                                                                                                      | ≈ 0.04             |
| Colour fastness                                                                     | EN 20-105 B02       |                                                                                                                                                                                                                                                                                                                                                         | ≥ 0.6              |
| Chemical products resistance                                                        | EN 423              |                                                                                                                                                                                                                                                                                                                                                         | Good               |
| Anti-bacterial and fungicidal treatment                                             |                     |                                                                                                                                                                                                                                                                                                                                                         | Yes                |
| Surface treatment                                                                   |                     |                                                                                                                                                                                                                                                                                                                                                         | PUR+ Protected     |
| CE MARKING                                                                          |                     |                                                                                                                                                                                                                                                                                                                                                         |                    |
|  | EN 14041            |     |                    |



Be connected!



#Jeoflor



## Jeoflor

Our related products!



Floor  
Self Leveling



Wall Coverings  
& Protections



Skirting &  
Profiles



Handrails

# Jeoflor

Alptahls GmbH, Bürgergasse 4, 8330 Feldbach, Austria. 

Tel. +43 (0)3152 370 49

info@jeoflor.com www.jeoflor.com

Toll Free : 18002028498